

CUSHMAN[®] TURF-TRUCKSTER[®]



The Cushman[®] Turf-Truckster[®] by Jacobsen[®] is the most rugged, easiest riding and best equipped turf vehicle on the market, featuring a heavy-duty carbon steel channel e-coated and powder painted frame and dent resistant rustproof body.

- **Heavy duty payload** of 2850 lbs. (1293 kg); steel or poly dumping beds available.
- **Choice of transmissions** with industry-exclusive automatic 3-speed transmission available; Dash-mounted shifter for automatic, 4-speed or 5-speed manual transmission.
- **Power for the rugged road ahead:** 33.8 hp (25.2 kW) EFI gas engine or 24.8 hp (18.5 kW) diesel engine available.
- **Full line of attachment options** including a top dresser, Core Harvester, spreader, blower, Quick Aerator and sprayer make the Turf-Truckster one of the most versatile vehicles on the market.

QUICK SPECS

Engine: Gas or Diesel

Rated Capacity: 2850 lbs. (1293 kg)

Drive Train: 4-speed manual, 5-speed manual, 3-speed automatic

Speed: 1 – 26 mph (1.6 – 41.8 km/h) depending on model

Dimensions:

Weight: 1742 – 1956 lbs. (790 - 887 kg)

Length 114.2 in. (2.9 m)

Height: 49 in. (1.2 m)

Width: 63.5 in. (1.61 m)



CHECK IT OUT!

Scan with your smart phone to view the Cushman[®] Turf-Truckster[®] gas product page. Get app using your smartphone at i-nigma.mobi

CUSHMAN® TURF-TRUCKSTER®

SPECIFICATIONS

Engine	Gas	Diesel
Type	Suzuki® 660 EFI, 3-cylinder, 4 cycle, 12 valve, liquid cooled electronic fuel injection	Kubota® D1105 diesel, 3-cylinder, 4-cycle, liquid cooled
Horsepower*	33.8 hp (25.2 kW) governed at 4450 rpm	24.8 hp (18.5 kW)
Air Cleaner	Donaldson® dry cartridge type with evacuator valve	
Lubrication	Fully pressurized system with full flow oil filter	
Fuel Capacity	7.0 gal. (26.5 L) unleaded	7.0 gal. (26.5 L) No. 2 diesel
Electrical System	60 amp, heavy duty alternator; 12 V starter with safety interlock	
Drive Train		
Clutch	6.7 in. (170 mm) dry, single disc and pressure plate	7.1 in. (180 mm) single disc and pressure plate
Manual Transmission	Five speed manual truck transmission with low-low (creeper) first gear; synchronized in all forward gears; two speed rear axle	Four speed manual truck transmission with low-low (creeper) first gear; synchronized in all forward gears; two speed rear axle
Automatic Transmission	Three speed automotive	
Tires, Brakes and Steering		
Front Tires	20 x 10-10, 4 ply rib tread	
Rear Tires	24 x 13-12, 4 ply turf tread	
Brakes	Heavy duty hydraulic, 7.9 in. (201 mm) duo-servo, self adjusting brakes on all wheels, with dual master cylinder and remote trunk-mounted master cylinder reservoir	
Steering	Automotive power steering	
Front Suspension	Double A-arm independent suspension with spring-over shock absorbers	
Rear Suspension	Heavy duty, multiple leaf springs with shock absorbers	
Maximum Capacity	2850 lbs. (1293 kg) Maximum capacity. For available payload capacity, subtract weight of driver, any passengers, ROPS and added accessories	
Speed		
Manual Transmission	1st gear: 1.4 - 4.3 mph (2.2 - 7.0 km/h) 2nd gear: 2.3 - 7.3 mph (3.7 - 11.8 km/h) 3rd gear: 3.6 - 11.6 mph (5.8 - 18.6 km/h) 4th gear: 5.5 - 17.5 mph (8.8 - 28.1 km/h) 5th gear: 6.9 - 22.1 mph (11.1 - 35.6 km/h) Reverse: 1.3 - 4.3 mph (2.2 - 6.9 km/h)	1st gear: 1.7 - 5.5 mph (2.7 - 8.8 km/h) 2nd gear: 3.2 - 10.2 mph (5.1 - 16.5 km/h) 3rd gear: 4.4 - 14.0 mph (7.0 - 22.5 km/h) 4th gear: 6.2 - 19.9 mph (10.0 - 32.1 km/h) Reverse: 1.8 - 5.7 mph (2.9 - 9.3 km/h)
Automatic Transmission	1st gear: 2.5 - 8.1 mph (4.1 - 13 km/h) 2nd gear: 4.5 - 14.4 mph (7.2 - 23.2 km/h) 3rd gear: 6.9 - 22.1 mph (11.1 - 35.6 km/h) Reverse: 3.1 - 9.9 mph (5 - 16 km/h)	
Weight and Dimensions		
Weight	Manual: 1808 lbs. (820 kg) Automatic: 1742 lbs. (790 kg)	Manual: 1956 lbs (887 kg)
Length	114.2 in. (2.9 m)	
Height	49 in. (1.2 m)	
Wheelbase	88.2 in. (2.2 m)	
Width	63.5 in. (1.61 m)	

*Engine horsepower is provided by engine manufacturer. Actual operating power output may vary due to conditions of specific use.

NOTE: Specifications, while correct at time of printing, may change without notice.

Utility Equipment

PRODUCT CONFIGURATION

EQUIPPED STANDARD

- ✓ 4 post ROPS with seat belt
- ✓ Liquid-cooled engine
- ✓ 2 speed rear axle
- ✓ Front underhood storage area
- ✓ Governor
- ✓ Hand throttle controls
- ✓ Headlights
- ✓ Horn
- ✓ Phone / cup holder
- ✓ 12V power plug outlet
- ✓ Cushman pin disconnect system
- ✓ Hydraulics with auxiliary outlets
- ✓ 4-ply turf tread rear tires

ACCESSORIES

- Flatbed, 47 in. (1.19 m) quick disconnect
- Box assembly, 47 in. (1.19 m) sides and tailgate with automatic tailgate release
- Box liner
- Flatbed 60 in. (1.52 m) quick disconnect
- Box assembly, 60 in. (1.52 m) sides and tailgate with automatic tailgate release
- Box assembly, poly box 42.5 in. L x 46 in. W x 13 in. Deep (1.08 m L x 1.17 m W x .33 m Deep)
- Top Dresser 1500 – Textured crescent belt with V guide
- Core Harvester for mounting to 47 in. (1.19 m) or 60 in. (1.52 m) steel bed
- Vicon Spreader
- Quick Aerator
- Implement Lift (“A” frame)
- Hitch, receiver style with drawbar – male insert 1.5 in. (3.81 cm)
- Drawbar (male insert only)
- Hitch, flat bar style
- Fifth wheel ball hitch including electric brake controller
- Axle Truss Kit
- Hydraulics, high/low (Gas and Diesel)
- PTO, heavy-duty, hydraulic
- PTO, heavy-duty, mechanical
- ROPS with seat belts and integrated canopy
- Cab, black with ROPS, windshield with wiper and rear window
- Doors, steel, Jacobsen orange
- Doors, steel, Ransomes green
- Heater/defroster
- Windshield with wiper
- Rear window
- Turf signals with right hand taillight
- Outside mirrors, right and left
- Front bumper
- Alarm, back-up kit, variable pitch
- Exhaust spark arrestor



1.888.922.TURF | www.jacobsen.com